

DINA

**Apparecchio da incasso a soffitto
costituito da:**

- Dissipatore in alluminio
- Anello in alluminio pressofuso verniciato
- Vetro di sicurezza trasparente
- Riflettore in alluminio satinato ad alta resa luminosa
- Sistema di fissaggio a molle
- Viti di chiusura in acciaio inox
- Verniciatura in polveri poliestere ad elevata resistenza ai raggi ultravioletti e alla corrosione

**Recessed ceiling luminaire
constructed of:**

- Housing: aluminium profile designed as a heat sink
- Die-cast painted aluminium cover plate
- Transparend safety glass
- Satin-matt faceted aluminium reflector with high luminous efficiency
- Spring fastening system
- Stainless steel screws
- Painting using high resistance to UV and corrosion polyester powders



Colori - Colours

X=2 Bianco
White

Diffusore - Diffuser


Codice-Code 00 1510

Codice-Code 00 1511


Codice-Code 00 1512

Classe energetica : vedi pag. 356


Energy class : see page 356




Incasso a soffitto
Recessed ceiling version



Entrata singola cavi di alimentazione
Single power supply cables input



LED
L'apparecchio necessita di alimentatore remoto elettronico (fornito)
The luminaire needs a remote power supplier (supplied)



IK 05



1510 MINI
1511 MIDI
1512 MAXI

MINI

● 1510.192	LED COB	20W	2000 lm	4000 K	52°
● 1510.172	LED COB	20W	1900 lm	3000 K	52°

MIDI

● 1511.192	LED COB	28W	2900 lm	4000 K	64°
● 1511.172	LED COB	28W	2800 lm	3000 K	66°

MAXI

● 1512.192	LED COB	36W	3500 lm	4000 K	90°
● 1512.172	LED COB	36W	3350 lm	3000 K	90°

● Con trasformatore remoto fornito / Remote power supply delivered

